



An
Employee
Owned
Company

5000-Watt

Industrial Gasoline

These industrial generators are an ideal choice for powering multiple tools, lights and other equipment contractors need on jobsites.



GEN-5000-0MK0

ALTERNATOR

- Total harmonic distortion (THD) less than 5%
- Copper windings

FRAME

- Powder coated wraparound frame
- Angled isolator design features six neoprene isolators

COMPONENTS

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone muffler
- Fuel shut-off valve
- Easy-to-read fuel gauge
- Heavy-duty industrial air cleaner
- Full power switch
- USDA/USFS-approved spark arrestors

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- CSA Certified

MODEL NUMBER	GEN-5000-0MH0+	GEN-5000-0MK0+
MAX. AC OUTPUT	5000 watts	5000 watts
RATED AC OUTPUT	4400 watts	4400 watts
DISPLACEMENT/ENGINE	270cc Honda GX270 OHV	277cc Kohler CH395 OHV
ALTERNATOR	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	41.7/20.8	41.7/20.8
CONT. AMPS (120V/240V)	36.7/18.3	36.7/18.3
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock
CIRCUIT BREAKERS	(2) 20A toggle circuit breakers, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breakers, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole
RATED SPEED	3600 RPM	3600 RPM
DECIBEL RATING	73.8	73.8
FUEL CAPACITY	5.7 gallons	5.7 gallons
RUN TIME (AT FULL LOAD)	6.8 hours	6.8 hours
DIMENSIONS (LxWxH)	29x19.75x22.5in.	29x19.75x22.5in.
SHIP WT.	198 lb.	198 lb.
NET WT.	176 lb.	176 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.
+49 state engine and/or fuel tank. Not for sale in California.

5000-Watt


Portable Generators – Industrial Gasoline

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODEL
32-0915	RV generator adapter – 30A/125V female/male. Use to connect RV cordsets to 30A generators.	All models
32-1289	Triple receptacle adapter – Converts (1) L5-30 plug to (3) lighted 5-20 locking receptacles	All models
AW-5090-0003	Lifting hook – For easier portability, folds down and out of the way when not in use	All models
AW-5740-0009	Wheel kit with flat-free tires – For easier mobility, two flat-free tires and rubber gripped handles	All models

OPTION: *Option must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODEL
GX-0004	Hour meter – Displays the number of hours unit has been in operation	All models



GFCI 5-20R



NEMA L14-20R
120V/240V



NEMA L5-30R
120VAC



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.