



An
Employee
Owned
Company

6000-Watt

Industrial Gasoline

These generators feature a wraparound frame for durability and are powered by OHV engines that are built to last.



GEN-6000-0MH0

ALTERNATOR

- Total harmonic distortion (THD) less than 5%
- Copper windings

FRAME

- Powder coated wraparound frame
- Angled isolator design features six neoprene isolators

COMPONENTS

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone muffler
- Fuel shut-off valve
- Easy-to-read fuel gauge
- Idle control
- Voltmeter/hour meter
- Heavy-duty industrial air cleaner
- USDA/USFS-approved spark arrestors

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- CSA Certified

MODEL NUMBER	GEN-6000-0MH0 ⁺	GEN-6000-0MK0 ⁺
MAX. AC OUTPUT	6000 watts	6000 watts
RATED AC OUTPUT	5000 watts	5000 watts
DISPLACEMENT/ENGINE	389cc Honda GX390 OHV	429cc Kohler CH440 OHV
ALTERNATOR	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	50.0/25.0	50.0/25.0
CONT. AMPS (120V/240V)	41.6/20.8	41.6/20.8
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock
CIRCUIT BREAKERS	(1) Main circuit breaker (2) 20A circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole	(1) Main circuit breaker (2) 20A circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole
RATED SPEED	3600 RPM	3600 RPM
DECIBEL RATING	77.1	77.1
FUEL CAPACITY	7.3 gallons	7.3 gallons
RUN TIME (AT FULL LOAD)	8.0 hours	8.0 hours
DIMENSIONS (LxWxH)	29x24.4x22.5in.	29x24.4x22.5in.
SHIP WT.	232 lb.	232 lb.
NET WT.	210 lb.	210 lb.


Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.
⁺49 state engine and/or fuel tank. Not for sale in California.

6000-Watt

Portable Generators – Industrial Gasoline

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODEL
32-0915	RV generator adapter – 30A/125V female/male. Use to connect RV cordsets to 30A generators.	All models
32-1289	Triple receptacle adapter – Converts (1) L5-30 plug to (3) lighted 5-20 locking receptacles	All models
AW-5090-0004	Lifting hook – For easier portability, folds down and out of the way when not in use	All models
AW-5740-0010	Wheel kit with flat-free tires – For easier mobility, two flat-free tires and rubber gripped handles	All models
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new	All models



GFCI 5-20R



NEMA L14-20R
120V/240V



NEMA L5-30R
120VAC



GEN-6000-0MH0



⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.