ePowerStation[™]

ePowerStation[™] is a high-capacity, eco-friendly and durable power source for situations where gas generators are not practical. Featuring a patent-pending eBox for easy customization. The ePowerStation[™] is great for food trucks, outdoor events, and construction projects, even indoors. With its tough tires, it's easy to move, no matter the terrain.



An Employee Owned Company







ePowerStation[™]

MODEL NUMBER	EPS-0305-0VF3M	EPS-0607-0VF3M
OUTPUT		
CONTINUOUS WATTAGE	3000 watts	6000 watts
MAX OUTPUT	9,000 watts (20sec.)	18,000 watts (10sec.)
VOLTAGE (AC)	120V	120V/240V
AMPERAGE	25A	50A/25A
FREQUENCY	60Hz	60Hz
PHASE	10	1Ø
CONNECTORS	See eBox receptacle configurations	See eBox receptacle configurations
BATTERY		
CAPACITY	5.0kWh	7.0kWh
VOLTAGE (DC)	48V	48V
TYPE	Lithium-ion	Lithium-ion
LIFECYCLES	2000 cycles to 80% capacity	2000 cycles to 80% capacity
SAFETY	Integrated BMS monitors individual cell voltge, current, resistance and temperature	

grated BMS monitors individual cell voltge, current, resistance and temperature UL 1642 Cell Safety Certification UN 38.3 Shipping Certification UL/IEC Pack Performance REACH and Battery Directive (2006/66/EC) Environmental Compliance FCC Title 47 CFR 15 Class B & CISPR 22-10 EMC/EMI Compliance

BATTERY CHARGER		
WATTAGE	3000 watts	3000 watts
VOLTAGE INPUT (AC)	120V/240V	120V/240V
AMPERAGE INPUT	16A/12.5A	16A/12.5A
FREQUENCY INPUT	60Hz	60Hz
PHASE INPUT	1Ø	10
CHARGING TIME: 0 to 100%	4 hours/2.5 hours	6 hours/3 hours
CHARGING TIME: 0 to 80%	2.7 hours/1.7 hours	4 hours/2 hours
UNIT		
OPERATING TEMPERATURES	14°F to 104°F	14°F to 104°F
CHARGING TEMPERATURES	32°F to 113°F	32°F to 113°F
STORAGE TEMPERATURES	-4°F to 140°F for up to 1 month -4°F to 77°F for up to 1 year	-4°F to 140°F for up to 1 month -4°F to 77°F for up to 1 year
DIMENSIONS (LxWxH)	45.125x24x35in.	45.125x24x35in.
NET WT.	250 lb.	305 lb.

eBox Receptacle Configurations

EBOX-0001-M

(1) 20A, 120V GFCI with USB and USB-C
(1) 30A, 120V twist lock
(1) 30A, 120V/240V twist lock

EBOX-0002-M

(1) 30A, 120V twist lock(2) 20A, 120V GFCI with USB and USB-C

EBOX-0003-M

(4) 20A, 120V GFCI with USB and USB-C

EBOX-0004-M

(1) 30A, 120V/240V twist lock(2) 20A, 120V GFCI with USB and USB-C

Limited Warranties

- 1 year inverter
- 2 year unit
- 3 year charger
- 8 year battery

Mi-T-M reserves the right to make component and design changes when necessary.

